

mayfair flags

vibrant granite appearance

- Manufactured with sparkling natural granite aggregates
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Significantly reduced efflorescence
- Creates a striking, contemporary look
- Step Flags are available



product specifications

Product type	Concrete Paving Flag																																				
Manufactured to	BS EN 1339:2003																																				
Surface layer	Hard wearing surface layer with a minimum of 4mm and >390kg/m ³ cement																																				
Granite content	Not less than 57% of granite aggregate in surface layer for Silver, Graphite and Russet; Not less than 46% of granite aggregate in surface layer for Sandstone; Not less than 32% of granite aggregate in surface layer for Rose																																				
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence																																				
Strength	Less than 50mm deep > 3.5MPa Greater than 50mm deep >5MPa (Class 3)																																				
Slip/Skid risk	Extremely Low (>75 USRV)																																				
Installed to	BS 7533-4:2006																																				
BSIplus	Q25 315																																				
Applications	Suitable for all pedestrian areas and traffic-free zones. Some of these specific sizes are suitable for occasional vehicular overrun. Always refer to BS 7533-8:2003 for guidance on the correct flag size to suit your application.																																				
Energy used	100% renewable energy																																				
Water used	100% water used from rainwater harvesting system																																				
Carbon Footprint * kgCO ₂ e/m ²	<table border="1"> <tr> <th></th> <th>35mm</th> <th>40mm</th> <th>50mm</th> <th>65mm</th> <th>70mm</th> </tr> <tr> <td>Silver</td> <td>14"</td> <td>16"</td> <td>19"</td> <td>24"</td> <td>30"</td> </tr> <tr> <td>Sandstone</td> <td>15"</td> <td>17"</td> <td>22"</td> <td>28"</td> <td>32"</td> </tr> <tr> <td>Graphite</td> <td>15"</td> <td>17"</td> <td>24"</td> <td>30"</td> <td>32"</td> </tr> <tr> <td>Russet</td> <td>15"</td> <td>17"</td> <td>22"</td> <td>32"</td> <td>32"</td> </tr> <tr> <td>Rose</td> <td>15"</td> <td>17"</td> <td>22"</td> <td>32"</td> <td>32"</td> </tr> </table>		35mm	40mm	50mm	65mm	70mm	Silver	14"	16"	19"	24"	30"	Sandstone	15"	17"	22"	28"	32"	Graphite	15"	17"	24"	30"	32"	Russet	15"	17"	22"	32"	32"	Rose	15"	17"	22"	32"	32"
	35mm	40mm	50mm	65mm	70mm																																
Silver	14"	16"	19"	24"	30"																																
Sandstone	15"	17"	22"	28"	32"																																
Graphite	15"	17"	24"	30"	32"																																
Russet	15"	17"	22"	32"	32"																																
Rose	15"	17"	22"	32"	32"																																
Recyclable	100% of this product can be recycled																																				
Recycled content (Not less than %)	<table border="1"> <tr> <th></th> <th>35mm</th> <th>40mm</th> <th>50mm</th> <th>65mm</th> <th>70mm</th> </tr> <tr> <td>Silver</td> <td>22%</td> <td>20%</td> <td>16%</td> <td>12%</td> <td>11%</td> </tr> <tr> <td>Graphite</td> <td>22%</td> <td>20%</td> <td>16%</td> <td>12%</td> <td>11%</td> </tr> <tr> <td>Russet</td> <td>22%</td> <td>20%</td> <td>16%</td> <td>-</td> <td>-</td> </tr> </table>		35mm	40mm	50mm	65mm	70mm	Silver	22%	20%	16%	12%	11%	Graphite	22%	20%	16%	12%	11%	Russet	22%	20%	16%	-	-												
	35mm	40mm	50mm	65mm	70mm																																
Silver	22%	20%	16%	12%	11%																																
Graphite	22%	20%	16%	12%	11%																																
Russet	22%	20%	16%	-	-																																
Manufacturing location	Produced in the UK with locally sourced materials																																				
breedim rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base.																																				

Tobermore products are manufactured in accordance with an accredited ISO 9001:2008 quality system. Manufacturing facilities are accredited to ISO14001:2004 Environmental Management. The company publish Environmental labels and declarations in accordance with BS EN ISO 14021:2001.

colours



Mayfair Flags Sandstone, Silver & Graphite

product	size (mm)	finish	edge	colours available	in stock	no. per m ²	no. per pack	weight (kg) per pack
MAYFAIR FLAGS BIM	600 x 600 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	2.78	20	859
			CHAMFERED	Graphite, Sandstone, Silver	YES	4.16	20	589
	450 x 450 x 70	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	15	512
			CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	20	470
	450 x 450 x 35	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	30	529
			CHAMFERED	Graphite, Sandstone, Silver, Rose, Russet	YES	6.25	25	384
	400 x 400 x 40	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver, Rose, Russet	YES	6.25	16	395
			CHAMFERED	Graphite, Silver	YES	6.25	16	395
	400 x 400 x 65	GRANITE TEXTURED	CHAMFERED	Graphite, Silver	YES	6.25	16	395
			CHAMFERED	Sandstone	MADE TO ORDER			

BIM This product is available to download from our website in **BIM Level 2** format.

Refer to all instructions and warnings on our website

visit www.tobermore.co.uk | call us 0844 800 5736 | follow us

27B18

sienna

vibrant granite appearance

- Manufactured with sparkling natural granite aggregates
- Superb hard-wearing granite surface
- Beautiful strong, vibrant colours
- Long-lasting colours
- Significantly reduced efflorescence
- Creates a striking, contemporary look

Modular sizes available. See Fusion.



product specifications

Product type	Concrete Paving Block																
Manufactured to	BS EN 1338:2003																
Surface Layer	Hard wearing surface layer with a minimum of 4mm and >350kg/m ³ cement																
Surface Finish	Textured Granite Aggregate																
Granite Content	Not less than 53% of granite aggregate in surface layer for Silver and Graphite; Not less than 45% of granite aggregate in surface layer for Sandstone.																
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence																
Strength	Typical tensile splitting strength of >3.6MPa and a failure load of >250N/mm																
Slip/Skid risk	Extremely Low (>75 USRV)																
Installed to	BS 7533-3:2005																
BSIplus	Q24 110																
Applications	Residential and Commercial when used in conjunction with the correct sub-base design in accordance with the latest British Standard.																
Energy used	100% renewable energy																
Water used	100% water used from rainwater harvesting system																
Carbon Footprint * kgCO ₂ e/m ²	<table border="1"> <tr> <th></th> <th>50mm</th> <th>60mm</th> <th>80mm</th> </tr> <tr> <td>Silver</td> <td>20"</td> <td>24"</td> <td>32"</td> </tr> <tr> <td>Sandstone</td> <td>22"</td> <td>26"</td> <td>34"</td> </tr> <tr> <td>Graphite</td> <td>22"</td> <td>26"</td> <td>34"</td> </tr> </table>		50mm	60mm	80mm	Silver	20"	24"	32"	Sandstone	22"	26"	34"	Graphite	22"	26"	34"
	50mm	60mm	80mm														
Silver	20"	24"	32"														
Sandstone	22"	26"	34"														
Graphite	22"	26"	34"														
Recyclable	100% of this product can be recycled																
Recycled content (not less than %)	<table border="1"> <tr> <th></th> <th>50mm</th> <th>60mm</th> <th>80mm</th> </tr> <tr> <td>Silver</td> <td>10%</td> <td>8%</td> <td>6%</td> </tr> <tr> <td>Graphite</td> <td>10%</td> <td>8%</td> <td>6%</td> </tr> </table>		50mm	60mm	80mm	Silver	10%	8%	6%	Graphite	10%	8%	6%				
	50mm	60mm	80mm														
Silver	10%	8%	6%														
Graphite	10%	8%	6%														
Manufacturing location	Produced in the UK with locally sourced materials																
breedim rating www.bre.co.uk	50/60mm: A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved when used in conjunction with a prepared recycled sub-base. 80mm: B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved when used in conjunction with a prepared recycled sub-base.																

Tobermore products are manufactured in accordance with an accredited ISO 9001:2008 quality system. Manufacturing facilities are accredited to ISO14001:2004 Environmental Management. The company publish Environmental labels and declarations in accordance with BS EN ISO 14021:2001.

colours



Important Information
Light coloured blocks emphasize tyre marks and oil spills. It must be accepted that these products will need more maintenance if the overall appearance is to be maintained.



Sienna Silver

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight (kg) per pack
SIENNA 50mm	208 x 173 x 50	Graphite, Sandstone, Silver	YES	14.04	2.34	27.79	390	1638
SIENNA DUO 50mm (both sizes in one pack)	208 x 173 x 50	Graphite, Sandstone, Silver	YES	13.86	0.99	30.3	210	1617
	173 x 173 x 50							
SIENNA 60mm	160 x 160 x 60	Graphite, Silver	YES	11.65	1.66	39.06	455	1646
	240 x 160 x 60	Graphite, Silver	MADE TO ORDER	12.48	2.49	26.04	325	1765
SIENNA DUO 60mm BIM (both sizes in one pack)	208 x 173 x 60	Graphite, Sandstone, Silver	YES	12.87	0.99	30.3	195	1818
	173 x 173 x 60							
SIENNA 80mm	240 x 160 x 80	Graphite, Silver	YES	9.6	1.92	26.04	250	1755
	160 x 160 x 80	Graphite, Silver	MADE TO ORDER	8.96	1.28	39.06	350	1639
	120 x 160 x 80	Graphite, Silver	YES	9.4	1.34	52.08	490	1719
	208 x 173 x 80	Graphite, Silver	MADE TO ORDER	10.07	1.44	27.79	280	1841
	173 x 173 x 80	Graphite, Silver	YES	9.9	0.99	30.3	150	1812

ML This product can be hand or machine laid. **BIM** This product is available to download from our website in **BIM Level 2** format.

Refer to all instructions and warnings on our website

visit www.tobermore.co.uk | call us 0844 800 5736 | follow us

23B18