

This drawing to be read in conjunction with all specifications and all other consultants design information. Any contradictions between this drawing and any other design information to be advised to the contract administrator and author immediately.

The contractor to site measure, check and verify all information issued, and confirm the correctness of the contents prior to the commencement on site.


The contractor to comply with all current statutory legislation, Building Regulations, British Standards, and good building practice.

Do not scale from this drawing.

Revision			
Rev	Description	Date	By / To



**Finishes Key**



**WALLS: W**

- W1** Fabric Wall Coverings - Tektura Range - Colour and range to be confirmed
- W2** Natural Derbyshire Stone Clad Wall
- W3** General Wall Paint - Dulux Professional Diamond Range. Colour to be confirmed  
N.B. All paint finishes to be scrubbable matt, Dulux Diamond range  
**W3F** Denotes painted feature wall. Colour to be confirmed
- W4** Feature Timber Cladding to Library to be confirmed by GNA
- W5** Feature Fireplace (Dimplex Aspen or equal approved for recessed fireplace + stone surround) allow
- W6** Feature Wall (Graphic) - Design to be confirmed

- W7** Altro White Rock Chameleon Range - Colour to be confirmed
- W8** Specialist Finish to Dry Store
- W9** Tiled areas - by ST3 Architectural - Colour and Range to be confirmed
- W10** IPS
- W11** Hardwood Framed Glazed Screens
- W12** Exposed Existing Brick Wall

**CEILING: C**

- C1** PLASTERBOARD  
British Gypsum Gyproc Wallboard 12.5mm
- C2** 600 x 600 CEILING TILE SYSTEM WITH PLASTERBOARD EDGES  
Non-fire rated fully accessible suspended ceiling system by Armstrong World Industries Ltd  
Tile: Armstrong Dune Supreme Tegular edge 600 x 600mm tile
- C3** ACOUSTIC BOARDS British Gypsum Gyptone Quattro 41 acoustic boards. Surrounding areas to be undertaken in wallboard.

- C4** 600 x 600 CEILING TILE SYSTEM  
Non-fire rated fully accessible suspended ceiling system by Armstrong World Industries Ltd  
Tile: Armstrong Dune Supreme Tegular edge 600 x 600mm tile
- C5** Metal tile ceiling, Armstrong
- C6** EXPOSED STRUCTURAL SOFFIT  
Thermally lined and sealed with Kingspan TP10 insulation board. Board to be mechanically fixed. Thickness tbc.
- C7** Bespoke Acoustic Timber fin feature ceiling between exposed feature 'King' trusses
- C8** GYPROC MOISTURE RESISTANT BOARD  
British Gypsum Gyproc 12.5mm

**ADDITIONAL REQUIREMENTS**  
\_R Ceiling to form lowered raft with 150mm overhang to allow installation LED tape

**ACCESS PANELS TO PLASTERBOARD CEILINGS**  
Size, number and approx. locations by M+E engineers

**SKIRTING: S**

- S1** Applies to Ceramic tiles to front of house WCs, Saloon and domestic kitchen: 100mm high covered set in skirting tile.
- S2** 100x13mm pencil edged MDF skirting to receive Eggshell paint finish.
- S3** Applies to Multi-purpose, Activity rooms and associated circulation: 120x13mm pencil edged H/W Skirting to receive Eggshell paint finish.
- S4** Applies to Kitchens, utility rooms, cleaners and store rooms: 100mm Altro PRC5100 set-in Cove Skirting.
- S5** Applies to Plant rooms: Epoxy Resin floor paint over cured concrete sealer take up min 200mm up wall face.
- S7** Applies to open plan public spaces where H/W timber flooring is used: 100x19mm Pencil edged H/W skirting to receive satin varnish finish.
- S8** Flush tiled skirting 100mm high to match tiled flooring

**Floor Finishes**

- F1** Recessed Primary heavy duty barrier matting with stainless steel trim (Gradus opguard 18mm closed construction double wipers with aluminium linking strips)
- F2** Recessed Secondary high performance barrier matting. Colour to match carpet
- F3** Lacquered oak timber strip floor (Junckers)
- F4** Nonslip timber effect vinyl (Itec safe Apex) - Collection: Camargue Colour: Golden Oak
- F5** Nonslip vinyl suitable for wet areas (Itec safe one) - Colour to be confirmed
- F6** Heavy contract grade broadloom carpet with impervious backing - JHS Hospi-classic Plus - Colour: 42 Biscuit
- F7** Heavy contract grade broadloom carpet with impervious backing - Universal Tones - Colour: Fawn
- F8** Epoxy paint (Watco safety coat or equal approved)
- F9** Floor Tiles for hairdressing, and front of house WC facilities, by ST3 Architectural - Colour and Range to be confirmed  
R11 finish (anti-slip). Tile to achieve slip resistance and water dispersal as manufacturer's recommendations. Colour to be confirmed.
- F10** Nonslip vinyl suitable for commercial kitchen areas - Altro Classic 25 (2.5mm)
- F11** Anti static heavy duty floor vinyl (Altro Walkway 20 SD)

\*Indication of stainless steel or PPC transition strips

client: Derbyshire County Council			
project: Belper Integrated Care and Library			
title: Ground Floor Finishes Plan			
date: May 2017	scale: 1:200 @A1	status: TENDER	
drawn by: HJ	checkd by: CJP	draw ref: 15019-GNA-XXX-00-MP-A-1800	rev: 
<small>© the drawing, design and the building works depicted are the copyright of Glancy Nicholls Architects Ltd &amp; may not be reproduced or amended, except by the written permission of Glancy Nicholls Architects Ltd. No liability will be accepted for any amendments made by other persons. The issue of this drawing/document does not confer any license for use of the design to any party whatsoever save as expressly agreed by Glancy Nicholls Architects Ltd.</small>			